



SPARTUS® EasyCUT 40s Compressor

COMPACT PLASMA CUTTER
WITH BUILT-IN COMPRESSOR



TECHNICAL PARAMETERS

Input [V]	Cutting current [A]	Max. cutting thickness [mm]	Duty cycle [%]	Recommended work pressure [bar]	Weight [kg]	Dimensions [mm]
230	20 – 40	20	35	4.5	13	510 × 185 × 295

DESCRIPTION

The **SPARTUS® EasyCUT 40s Compressor** is a compact inverter plasma cutter designed for cutting metals and other electrically conductive materials. It combines modern technologies with a lightweight and portable design and is powered by a single-phase 230V network. The **SPARTUS® EasyCUT 40s Compressor** functions both as a plasma cutter and an electrode welding machine.

PLASMA CUTTING

The **EasyCUT 40s Compressor** allows for cutting current adjustment within the range of 20 - 40A, perfectly adapting to user needs. The maximum thickness of the cut material is 20mm. The device features 2T/4T microswitch modes and post-gas adjustment. The contactless pilot arc initiation system without HF ensures excellent quality and extended lifespan of consumables.

An **integrated compressor** provides the compressed air necessary to generate a plasma arc, enabling fieldwork. A button on the front panel allows for easy switching of the air supply source.

The cutter has two operating modes:

- **STANDARD CUTTING** is the basic mode in which the plasma stream continuously cuts the material, allowing for quick and precise cutting of metal or other conductive materials to the desired shape and size. It is the most commonly chosen option for tasks requiring smooth and even cutting edges.
- **INTERMITTENT CUTTING** is a specialized mode particularly useful for cutting materials with irregular surfaces, such as mesh. This function allows the cutter to maintain a stable plasma arc even when there are interruptions in contact with the material. This enables continuous cutting without the need for manual re-ignition of the arc at each break, a typical challenge when processing meshes and similar materials. Using intermittent cutting mode significantly facilitates and accelerates the cutting process while minimizing the risk of damaging the device due to frequent arc losses and resumptions. This solution greatly enhances work efficiency, allowing for smooth and effective cutting even in complex and demanding tasks.


WELDING

The **EasyCUT 40s Compressor** enables coated electrode welding (MMA), which is widely used in various conditions and is ideal for steel and cast iron. The welding current adjustment in the EasyCUT 40s Compressor ranges from 30 to 140A, allowing flexible adjustment of parameters for various welding tasks. The device also features support functions for MMA welding, such as **HOT START**, **ARC FORCE** and **VRD**.

The **SPARTUS® EasyCUT 40s Compressor** is the perfect solution for users who value mobility and reliability.



SPARTUS® EasyCUT 40s Compressor



PACKAGE EQUIPMENT:

plasma torch SPARTUS® 45H 4m

electrode holder

work clamp

user's manual

