



TECHNICAL PARAMETERS

Input [V]	Cutting current [A]	Max. cutting thickness [mm]	Duty cycle [%]	Recomended work pressure [bar]	Air consumption [l/min]	Weight [kg]	Dimensions [mm]
400	20 - 70	25	60	5,5	170	19.4	540 × 220 × 370

SPARTUS® Master CUT 70H. Professional, inverter plasma cutter, constructed on the basis of IGBTs. Designed for cutting metals and other electrically conductive materials. It is powered from three-phase 400V source power.


Modern, dependable and exceptionally lightweight (approx. 30% lighter than other plasma cutters with similar power). Cutting current between 20 - 70A, allows to cut materials up to 25mm thickness.

SPARTUS® MasterCUT 70H cutter is equipped with control panel with digital display parameters. It has infinitely adjustable cutting current and Post gas function (longer life of plasma torch). Built-in professional HF arc ignition system, overload control system and parameters stabilization system, provides excellent cutting quality in all conditions.

Examples of use: light industrial, workshop, portable repair, production.



SPARTUS® MasterCUT 70H



MASTER

PACKAGE EQUIPMENT:

Handy plasma torch SPARTUS® 70H 6m

(type: CEBORA® P70 / EWS® EX60)

With toolbox (free consumables kit)

Air filter with the pressure control

3m work clamp

Gas hose

User's manual

